


# SK-250F



## HIGH POWER CINEMA SURROUND SPEAKER FOR DIGITAL APPLICATIONS



### SPECIFICATION

Frequency Response	: 65Hz~16kHz
Power Rating	: 250 Watts Continuous Pink Noise, 1000 Watts Peak
Sensitivity	: 96 dB SPL, 1W @ 1m
Nominal Impedance	: 8 Ohms
Hor.Coverage Angle	: 90° Average 4000 Hz to 12kHz
Vert.Coverage Angle	: 60° Average 4000 Hz to 12kHz
Crossover Frequency	: 2.2 KHz
Polarity	: EIA (Positive Voltage to RED Terminal Gives Forward Cone Motion)

### Low Frequency Transducer

Model	: CS-10
Nominal Diameter	: 250 mm (10Inch)

### High Frequency Transducer

Model	: PA-D25
Nominal Diameter	: 25 mm. (1 Inch)

### Physical:

Downward Firing Angle	: Normal 20° When Mounted Flush on Back Panel
Enclosure Material	: Textured Black H.I.P.S. Plastic
Grill	: Metal Mesh, Black Powder Coating
Input Connectors	: Black / Red Binding Posts
Dimension (H x W x D)	: 495 mm x 495 mm x 300 mm (19.5 in x 1.5 in x 11.8 in)
Rigging / Fitting	4 x Recessed 0.25in Mounting 1 x 35 mm Integral Pole Mounting Socket
Net Weight	: 9.5 kg
Gross weight	: 11.2 kg

